



# 25.6V 200AH LITHIUM BATTERY

## ► Features

- A grade brand new prismatic LiFePO4 cells
- Over charge, over discharge, over temperature, low Temperature, over current and short circuit protection
- Cell balance function
- Certificate: UN38.3, MSDS
- $\geq 4000$  cycles @80% DOD(25°C, 0.5C )
- Easy installation and maintenance free
- IP65, superior safety
- Max.2 battery packs can be connected in series

## ► Electrical Characteristics

Model	LFP5.12KWH25.6V-P65L2RP40
Battery Type	LiFePO4
Nominal Voltage (V)	25.6
Nominal Capacity (AH)	200
Energy (WH)	5120
Pack Mode	8S1P
Continuous Discharge Current (A)	150
Charge Cut-off Voltage (V)	28.8
Discharge Cut-off Voltage (V)	20.8
Max.Charge Current (A)	100@30min
Max.Discharge Current (A)	200@30min
Peak Discharge Current (A)	240A@10S
Recommend Discharge Current (A)	100
Recommend Discharge Depth (%)	80
Cycle Life	$\geq 4000$ cycles (25°C, 0.5C ) 80% DOD
Communication	—
Charge&Discharge Temperature (°C)	Charge: 0°C~+55°C / Discharge: -20°C~+60°C
Optimal Storage Temperature (°C)	5°C ~ +35°C
Recommend Storage Humidity	20%~80%
Terminal	M8
Dimensions (L*W*H) (mm)	523*269*218
Weight (Kg)	46±0.5
Transportation	UN38.3, MSDS
IP Class	IP65