



UT352

UT352 sound level meter can measure noise level and output results in dB. A range of weighted modes can be selected depending on the application. UT352 consumes very little power and can continuously work up to 20 hours. They are suitable for industrial and environmental sound level measurements.

Specifications	Range	UT352
<b>Certificates</b>	<b>CE, UKCA</b>	
Range	30~130dB	
Accuracy	±1.5dB	
Frequency	31.5Hz~8000Hz	
Frequency weighting	A&C	
Sampling rate (Fast)	8 times/s	
Sampling rate (Slow)	1 time/s	
Data storage	63	
Analog outputs (AC)	0.707Vrms full scale; Output impedance: around 600Ω	
Analog outputs (DC)	2Vrms full scale; 10mV/dB; Output impedance: around 100Ω	

**Features**

- Powered by batteries or external power source
- Data hold
- LCD backlight
- A (ear)/C (machine) weighted modes
- Auto power off (cancelable)
- 63 sets of data storage
- AC/DC analog signal output
- Simulated analog bar
- Manual/auto range selectable
- Analog bar graph: 30~130dB
- Low battery indication: ≤4.8V
- MAX/MIN
- High/low alarm

**Characteristics**

Standard accessories	Windscreen, leather box, English manual
Power	1.5V battery (LR6) x 4
Display	53 x 41mm
Product size	273 x 70 x 39mm
Product net weight	330g
Standard individual packing	Gift Box
Standard quantity per carton	10pcs
Standard carton measurement	670 x 415 x 120mm
Standard carton gross weight	7.3kg